

P201 - FFP2 Valved Respirator

Collection: Disposable Mask FFP2

Range: Disposable Masks

Materials: Polypropylene

Inner Pack: 10

Outer Carton: 30

Product information

Protects against fine toxic dust, fumes and water based mists. The respirator can be used in concentrations of contaminants up to 10 times the WEL. All the qualities of the P200 with an added exhalation valve.

Disposable Mask FFP2

Disposable mask FFP2 level, protects against solid and liquid particles of average toxicity. Minimal % of filtration 94%. Protects up to 10 times the TLV (Assigned Protection Factor for FFP2 masks). Examples of applications: Sanding of soft wood, composite materials, rust, putty, plaster, plastics /cutting, deburring, grinding, drilling of metal. Our Biztex brand ensures exceptional quality and performance across our full range of disposable masks.

Disposable Masks

Our Biztex™ brand ensures exceptional quality and performance across our full range of disposable masks. The extensive Biztex range offers a high level of protection and quality safeguarding the wearer against many workplace risks including liquid chemicals, static electricity, dry particles and radioactive contamination. The complete Biztex range includes disposable masks and limited-life garments.

Standards

AS/NZS 1716 (P2)

NIOSH N95

EN 149 FFP2 (NR)



Features

- CE-CAT III
- Ultrasound welded elastic strap
- High performance exhalation valve to reduce heat and provide comfort when used in hot and humid conditions
- Large inner space to help the user to breathe more easily
- Retail box which aids presentation for retail sales
- Ideal for all day use

Colours

	Range
White	-

PORTWEST®

PRODUCT SPECIFICATION & TECHNICAL DATA

P201 - FFP2 Valved Respirator

Commodity Code: 6307909810

Test House

BSI Group The Netherlands B.V. (Notified Body No.: 2797)

Say Building, John M. Keynesplein 9, 1066 EP

, Netherlands

Cert No: 714896

CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m ³)	EAN13	DUN14
P201WHR	White	66.0	43.0	36.0	0.2400	0.1022	5036108160006	15036108635808